



<b>10027-O Product Data Sheet</b>	
-----------------------------------	--

Part Number:	10027-O
Nomenclature:	15" x 18" Oil Only, Medium Weight, melt-blown, bonded polypropylene sorbent pad.
Unit Color:	White
Unit Dimensions:	15" width x 18" length. (270 sq inches / .2083 sq yards.)
Unit Weight:	1.46 oz per pad. ( 7 ospy (oz per square yard))
Unit Absorbency:	17.52 oz to 21.9 oz (viscosity of fluid may raise or lower this base)
Units per Case /Bale:	100 pads per bale
Case / Bale Absorbency:	13.67 gallons to 17.11 gallons (viscosity of fluid may raise or lower this base)
Case / Bale Weight:	9.13 lbs.
Case / Bale Dimensions:	15" x 18" x 10"
Case / Bale per Pallet:	40 bales per pallet (8 cases per tier / 5 tiers per pallet.)
Pallet Dimensions:	48" x 48" x 90"
Pallet Weight:	400.2 lbs.

**Features:**

Absorbent pad that is specifically designed to selectively absorb Hydrocarbon based fluids, such as motor oil, diesels, kerosene, hydraulic oil, pesticides and many other petroleum based liquids, without absorbing water.

- Absorbs petroleum and petroleum based liquids such as lubricants, fuels and pesticides without absorbing aqueous solutions (water based liquids).
- Specially bonded material to give added strength for tough jobs.
- Repels water while afloat to clean up spills on water (Hydrophobic).
- The natural white color draws attention to machine leaks and alerts the user of the current saturation level of the pads during a spill cleanup.
- ProSorbents™ Fiber technology is specifically designed to handle demanding tasks and large volume cleanups.
- Pads are ideal for catching drips and soaking up spills.
- Flame-resistant material won't burn immediately like cellulose absorbents. ProSorbent™ oil only pads melts when exposed to high heat while on the job.
- Can be wrung out and incinerated after use to reduce waste or for fuels blending.

**Regulations and Compliance**

29 CFR 1910.22 (a)(2)	“The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition. Where wet processes are used, drainage shall be maintained and false floors, platforms, mats, or other dry standing places should be provided where practicable.”
-----------------------	---

Prepared / Updated: March 17<sup>th</sup>, 2010