



13029-O Product Data Sheet	
-----------------------------------	--

Part Number:	13029-O
Nomenclature:	36" x 34" Oil Only, melt-blown polypropylene, bonded sorbent pad.
Unit Color:	White
Unit Dimensions:	36" width x 34" length. (1224 sq inches / .944 sq yards.)
Unit Weight:	8.499 oz per pad. (9 ospy (oz per square yard))
Unit Absorbency:	106.25 to 185.79 oz (viscosity of fluid may raise or lower this base)
Units per Case /Bale:	50 pads per bale
Case / Bale Absorbency:	41.50 to 72.57 gallons (viscosity of fluid may raise or lower this base)
Case / Bale Weight:	26.56 lbs.
Case / Bale Dimensions:	36" x 34" x 8"
Case / Bale per Pallet:	15 bales per pallet
Pallet Dimensions:	48" x 48" x 48"
Pallet Weight:	435 lbs.

Features:

Absorbent pad that is specifically designed to selectively absorb Hydrocarbon based fluids, such as motor oil, diesels, kerosene, hydraulic oil, pesticides and many other petroleum based liquids, without absorbing water.

- Absorbs petroleum and petroleum based liquids such as lubricants, fuels and pesticides without absorbing aqueous solutions (water based liquids).
- Specially bonded material giving added strength for tough jobs.
- Repels water while afloat to clean up spills on water (Hydrophobic).
- The natural white color draws attention to machine leaks and alerts the user of the current saturation level of the pads during a spill cleanup.
- ProSorbents™ Fiber technology is specifically designed to handle demanding tasks and large volume cleanups.
- Pads are ideal for catching drips and soaking up spills.
- Flame-resistant material won't burn immediately like cellulose absorbents. ProSorbent™ oil only pads melts when exposed to high heat while on the job.
- Can be wrung out and incinerated after use to reduce waste or for fuels blending.

Regulations and Compliance

29 CFR 1910.22 (a)(2)	<p>“The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition. Where wet processes are used, drainage shall be maintained and false floors, platforms, mats, or other dry standing places should be provided where practicable.”</p>
-----------------------	--

Prepared / Updated: March 17th, 2010