



24025-U Product Data Sheet	
-----------------------------------	--

Part Number:	24025-U
Nomenclature:	15" x 18" Universal, Light Weight, melt-blown, bonded polypropylene sorbent pad.
Unit Color:	Gray
Unit Dimensions:	15" width x 18" length. (270 sq inches / .2083 sq yards.)
Unit Weight:	1.042 oz per pad. (5 ospy (oz per square yard))
Unit Absorbency:	10.42 oz to 14.59 oz (viscosity of fluid may raise or lower this base)
Units per Case /Bale:	200 pads per bale
Case / Bale Absorbency:	16.28 gallons to 22.80 gallons (viscosity of fluid may raise or lower this base)
Case / Bale Weight:	13.025 lbs.
Case / Bale Dimensions:	15" x 18" x 14"
Case / Bale per Pallet:	30 bales per pallet (6cases per tier / 5 tiers per pallet.)
Pallet Dimensions:	48" x 48" x 94"
Pallet Weight:	425.75 lbs.

Features:

Absorbent pad that is designed to absorb oil and water base liquids such as motor oil, diesels, coolants, acids and caustics.

- Specially bonded material to give added strength for tough jobs.
- Absorbs all forms of liquid.
- The gray color hides unsightly messes.
- ProSorbents™ Fiber technology is specifically designed to handle demanding tasks and large volume cleanups.
- Pads are ideal for catching drips and soaking up spills.
- Flame-resistant material won't burn immediately like cellulose absorbents. ProSorbent™ oil only pads melts when exposed to high heat while on the job.
- Can be wrung out and incinerated after use to reduce waste or for fuels blending.

Regulations and Compliance

29 CFR 1910.22 (a)(2)	“The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition. Where wet processes are used, drainage shall be maintained and false floors, platforms, mats, or other dry standing places should be provided where practicable.”
-----------------------	---

Prepared / Updated: March 17th, 2010