



31027-O Product Data Sheet	
Part Number:	31027-O
Nomenclature:	36" x 144' SMS oil only, medium weight, melt-blown, bonded polypropylene sorbent roll. Three layer construction.
Unit Color:	White
Unit Dimensions:	36" width x 144' length. (62,208 sq inches / 48 sq yards.)
Unit Weight:	27 lbs. per roll. (10 ospy (oz per square yard))
Unit Absorbency:	33.75 gal to 50.625 gal. (viscosity of fluid may raise or lower this base)
Units per Case /Bale:	1 roll per bale
Case / Bale per Pallet:	18 bales per pallet (9 bales per tier / 2 tiers per pallet.)
Pallet Dimensions:	48" x 48" x 90"
Pallet Weight:	521 lb.

Features:

Our own Pro-Fine Fiber™ technology is a unique process that is used in our Technical and Medical Grade products that when used with approved resin, the final product meets and complies with FDA requirements. This process is also used in our absorbent products creating highly absorbent and strong fine fiber material.

- Specially bonded material to give added strength for tough jobs.
- Designed for non-linitng applications.
- Repels water while afloat to clean up spills on water (Hydrophobic).
- The natural white color draws attention to machine leaks and alerts the user of the current saturation level of the pads during a spill cleanup.
- ProSorbents™ Fiber technology is specifically designed to handle demanding tasks and large volume cleanups.
- Flame-resistant material won't burn immediately like cellulose absorbents. ProSorbent™ oil only pads melts when exposed to high heat while on the job.
- Can be wrung out and incinerated after use to reduce waste or for fuels blending.

Regulations and Compliance

29 CFR 1910.22 (a)(2)	“The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition. Where wet processes are used, drainage shall be maintained and false floors, platforms, mats, or other dry standing places should be provided where practicable.”
-----------------------	---

Prepared / Updated: March 17th, 2010