



Product Data Sheet	
Part Number	SPIR150
Nomenclature:	Industrial Needle Punch Sorbent Felt Rolls With Barrier Coating
Unit Color:	Black / Gray
Unit Dimensions:	36" x 150"
Unit Weight:	30 lbs
Unit Absorbency:	20 gallons to 30 gallons
Units per Case /Bale:	1 roll
Units per Pallet:	18
Pallet Dimensions:	48" x 48" x 96"
Pallet Weight:	345 lbs..

Description:

ProSorbent industrial rug is designed for use around machinery where oils and solvents are used and spilled. The industrial needle punch felt has a strong attraction towards hydrocarbons. With the non-slip barrier, liquids will not pass through to the surface you are trying to protect, and the non-slip properties reduces the chance of slip and fall in wet conditions.

Features:

- Can be incinerated as a fuel at 8900 btu's.
- Can hold up to heavy foot and forklift traffic.
- Needle Punched for great strength.

Attribute	Test Method	Cross Directional	Machine Directional	Typical
Weight	ASTM D3776			8 oz/sy
Tensile Strength (Grab) lbf	ASTM D5034	405.7	325.9	
Tensile Strength (Strip) lbf	ASTM D5035	129.0	133.5	
Elongation, %	ASTM D1117	165.6	104.8	
Tear Strength, lbf	ASTM D5035	85.8	80.6	
Ball Burst, lbf				370.3
Capacity per sq. yrd.		(10W30 Motor Oil)		51 (fl oz)

Regulations and Compliance

40 CFR 112.7	SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.
40 CFR 122.26	When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

Prepared / Updated: Sept 19, 2011